


ZipTwo™ | 707

707-Z2-4-48-X-X-X-0-Z-SO-35-S2-0-BL

The performance data in black text is confirmed through third party testing (see the following Light Laboratory report for details). The performance data in grey text is calculated by Vode, for reference only.

Technical Support: (707) 996-9898



Details

Rail Type / Length	ZipTwo, 48"
LED Type	Zipper Board
Lumen Output	Standard Output
Color Temperature	3500K, 80+ CRI
Optics	60° Black Symmetric

Performance Summary

	2700K	3000K	3500K	4000K
Color Temperature	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	56	58	59	60
Total Lumens, 4' rail (1219mm)	1443	1489	1519	1550
Lumens per foot (305mm)	361	372	380	387
Input Power (W), 4' rail (1219mm)	26.1	26.1	26.1	26.1
Watts per foot (305mm)	6.6	6.6	6.6	6.6
CRI	-	-	85	-

© 2017 Vode Lighting LLC. All rights reserved. The Vode logo and Vode, are either registered trademarks or trademarks of Vode Lighting LLC in the United States and/or other countries. All other brand or product names are trademarks or registered trademarks of their respective owners. No part of the above drawing, design, arrangements or ideas thereon shall be duplicated or used for any purpose whatsoever without the express permission of Vode Lighting LLC. Due to ongoing innovation, specifications may change without notice.



IES INDOOR REPORT
PHOTOMETRIC FILENAME : VODE_707_Z2_SO_35_S2-BL.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002
[TEST] L071704228 (SOURCE REPORT FOR REFERENCE)
[TESTLAB] REPORT BASED ON DATA PRODUCED BY NVLAP ACCREDITED LAB
[ISSUEDATE] 11/1/2017
[MANUFAC] Vode Lighting
[LUMCAT] 707-Z2-48-Z-SO-35-S2-BL
[LUMINAIRE] ZipTwo LED, 48", 3500K, 80 CRI, zipper board,
[MORE] 60° black symmetric lens, standard output
[TEST PROCEDURE] IESNA:LM-79-08

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	1515
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	58
Total Luminaire Watts	26.16
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	0.82
Spacing Criterion (90-270)	1.16
Spacing Criterion (Diagonal)	0.98
Basic Luminous Shape	Rectangular
Luminous Length (0-180)	0.02 ft
Luminous Width (90-270)	4.02 ft
Luminous Height	0.00 ft

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	24329	47654	91849
55	11282	24490	53933
65	6349	13444	29130
75	4269	8537	17075
85	3622	5433	9054

IES INDOOR REPORT
PHOTOMETRIC FILENAME : VODE_707_Z2_SO_35_S2-BL.IES

CANDELA TABULATION

	<u>0</u>	<u>5</u>	<u>10</u>	<u>15</u>	<u>20</u>	<u>25</u>	<u>30</u>	<u>35</u>	<u>40</u>	<u>45</u>
0.0	1182.36	1182.36	1182.36	1182.36	1182.36	1182.36	1182.36	1182.36	1182.36	1182.36
1.0	1182.36	1181.18	1182.36	1182.36	1182.36	1182.36	1182.36	1182.36	1182.36	1182.36
3.0	1176.46	1176.46	1176.46	1176.46	1176.46	1176.46	1177.64	1177.64	1177.64	1178.82
5.0	1162.30	1162.30	1162.30	1163.48	1163.48	1164.66	1165.84	1167.02	1168.20	1169.38
7.0	1141.06	1141.06	1142.24	1143.42	1144.60	1146.96	1149.32	1151.68	1154.04	1156.40
9.0	1109.20	1109.20	1110.38	1112.74	1115.10	1118.64	1123.36	1126.90	1131.62	1136.34
11.0	1069.08	1070.26	1071.44	1074.98	1078.52	1084.42	1090.32	1096.22	1103.30	1111.56
13.0	1021.88	1023.06	1025.42	1030.14	1036.04	1043.12	1051.38	1059.64	1070.26	1079.70
15.0	967.60	968.78	972.32	977.04	985.30	994.74	1005.36	1017.16	1030.14	1044.30
17.0	908.60	909.78	914.50	921.58	931.02	942.82	955.80	971.14	987.66	1004.18
19.5	827.18	828.36	834.26	842.52	854.32	868.48	885.00	905.06	925.12	946.36
22.5	723.34	724.52	731.60	741.04	755.20	772.90	794.14	817.74	842.52	869.66
25.5	615.96	618.32	625.40	637.20	652.54	673.78	696.20	723.34	754.02	784.70
29.0	494.42	496.78	505.04	516.84	533.36	555.78	581.74	611.24	644.28	680.86
33.0	369.34	371.70	378.78	390.58	407.10	429.52	455.48	486.16	522.74	560.50
37.5	252.52	254.88	260.78	271.40	285.56	305.62	329.22	357.54	391.76	428.34
42.5	159.30	160.48	165.20	172.28	184.08	199.42	218.30	241.90	270.22	302.08
47.5	97.94	99.12	102.66	107.38	115.64	126.26	139.24	156.94	178.18	201.78
55.0	48.38	48.38	50.74	53.10	57.82	62.54	70.80	79.06	90.86	105.02
65.0	20.06	20.06	21.24	22.42	23.60	25.96	28.32	33.04	37.76	42.48
75.0	8.26	8.26	8.26	8.26	9.44	10.62	11.80	12.98	14.16	16.52
85.0	2.36	2.36	2.36	2.36	2.36	2.36	2.36	3.54	3.54	3.54
90.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

Vert. Angles **Horizontal Angles**

	<u>50</u>	<u>55</u>	<u>60</u>	<u>65</u>	<u>70</u>	<u>75</u>	<u>80</u>	<u>85</u>	<u>90</u>
0.0	1182.36	1182.36	1182.36	1182.36	1182.36	1182.36	1182.36	1182.36	1182.36
1.0	1182.36	1182.36	1182.36	1182.36	1182.36	1182.36	1182.36	1182.36	1182.36
3.0	1178.82	1178.82	1180.00	1180.00	1180.00	1180.00	1180.00	1181.18	1180.00
5.0	1170.56	1171.74	1172.92	1174.10	1175.28	1176.46	1176.46	1177.64	1177.64
7.0	1159.94	1162.30	1164.66	1167.02	1169.38	1170.56	1171.74	1172.92	1172.92
9.0	1141.06	1145.78	1150.50	1154.04	1157.58	1159.94	1162.30	1163.48	1163.48
11.0	1118.64	1125.72	1131.62	1137.52	1143.42	1148.14	1150.50	1152.86	1152.86
13.0	1090.32	1100.94	1110.38	1118.64	1125.72	1131.62	1136.34	1138.70	1139.88
15.0	1057.28	1070.26	1083.24	1095.04	1104.48	1112.74	1118.64	1122.18	1123.36
17.0	1021.88	1038.40	1054.92	1069.08	1080.88	1091.50	1098.58	1103.30	1105.66
19.5	968.78	990.02	1011.26	1030.14	1045.48	1059.64	1069.08	1074.98	1077.34
22.5	896.80	923.94	951.08	974.68	995.92	1013.62	1025.42	1032.50	1036.04
25.5	817.74	850.78	882.64	912.14	936.92	958.16	974.68	984.12	987.66
29.0	718.62	756.38	794.14	829.54	860.22	886.18	905.06	916.86	920.40
33.0	601.80	643.10	685.58	724.52	758.74	788.24	810.66	823.64	828.36
37.5	468.46	512.12	554.60	595.90	632.48	664.34	687.94	702.10	708.00
42.5	337.48	376.42	415.36	454.30	487.34	518.02	540.44	554.60	559.32
47.5	230.10	260.78	291.46	323.32	351.64	377.60	396.48	408.28	411.82
55.0	121.54	138.06	156.94	175.82	193.52	208.86	221.84	228.92	231.28
65.0	48.38	55.46	63.72	70.80	77.88	83.78	88.50	92.04	92.04
75.0	18.88	21.24	23.60	25.96	28.32	30.68	31.86	33.04	33.04
85.0	3.54	4.72	4.72	4.72	5.90	5.90	5.90	5.90	5.90
90.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

IES INDOOR REPORT
PHOTOMETRIC FILENAME : VODE_707_Z2_SO_35_S2-BL.IES

ZONAL LUMEN SUMMARY

Zone	Lumens	%Lamp	%Fixt
0-20	384.85	N.A.	25.40
0-30	734.70	N.A.	48.50
0-40	1025.9	N.A.	67.70
0-60	1385.43	N.A.	91.40
0-80	1502.03	N.A.	99.10
0-90	1515.23	N.A.	100.00
10-90	1425.43	N.A.	94.10
20-40	641.05	N.A.	42.30
20-50	887.96	N.A.	58.60
40-70	441.08	N.A.	29.10
60-80	116.60	N.A.	7.70
70-80	35.05	N.A.	2.30
80-90	13.19	N.A.	0.90
90-110	0.00	N.A.	0.00
90-120	0.00	N.A.	0.00
90-130	0.00	N.A.	0.00
90-150	0.00	N.A.	0.00
90-180	0.00	N.A.	0.00
110-180	0.00	N.A.	0.00
0-180	1515.23	N.A.	100.00

Total Luminaire Efficiency = N.A.%

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	89.79
10-20	295.06
20-30	349.85
30-40	291.20
40-50	246.91
50-60	112.62
60-70	81.55
70-80	35.05
80-90	13.19
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00


IES INDOOR REPORT
PHOTOMETRIC FILENAME : VODE_707_Z2_SO_35_S2-BL.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	111	108	104	102	109	106	103	100	101	99	97	98	96	94	94	93	91	89
2	104	97	92	88	101	96	91	87	92	88	85	89	86	83	86	83	81	79
3	97	88	82	77	95	87	81	76	84	79	75	82	77	74	79	76	72	71
4	90	81	74	68	88	79	73	68	77	71	67	75	70	66	73	69	65	63
5	84	74	67	61	83	73	66	61	71	65	60	69	64	60	67	63	59	57
6	79	68	61	55	77	67	60	55	65	59	55	64	58	54	63	58	54	52
7	74	63	55	50	73	62	55	50	61	54	50	59	54	50	58	53	49	48
8	70	58	51	46	68	58	51	46	56	50	46	55	50	46	54	49	45	44
9	66	54	47	42	65	54	47	42	53	47	42	52	46	42	51	46	42	40
10	62	51	44	39	61	50	44	39	49	43	39	49	43	39	48	43	39	37

POLAR GRAPH



Maximum Candela = 1182.36 Located At Horizontal Angle = 0, Vertical Angle = 0
1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (0) (Through Max. Cd.)