

ZipTwo | 707

How to Specify Low Glare

See [Power Guide](#) for driver features & limitations.

LED Type: Z Zipper Board

| Lumen Output | Color Temperature | Optics | Sensors |
|--|--|---|--|
| LO Low Output | 80+ CRI | Low Glare | 0 None |
| SO Standard Output | 27 2700K | BAGB Asymmetric Wallwash Graphite Baffle | ZZ Other (please specify) ⁵ |
| HO High Output | 30 3000K | BAWB Asymmetric Wallwash White Baffle | |
| ZZ Other (please specify) | 35 3500K | B1GB 25° Symmetric Graphite Baffle | |
| See IES Files page for details. | 40 4000K | B1WB 25° Symmetric White Baffle | |
| See Power Guide for driver features & limitations. | 90+ CRI | B2GB 60° Symmetric Graphite Baffle | |
| | 279 2700K | B2WB 60° Symmetric White Baffle | |
| | 309 3000K | B3GB 120° Diffuse Graphite Baffle | |
| | 359 3500K | B3WB 120° Diffuse White Baffle | |
| | 409 4000K | B4GB Bisymmetric Graphite Baffle | |
| | | B4WB Bisymmetric White Baffle | |
| | ZZ Tunable White Available | | |
| | See Guide for details. | | |

Finish Options

| | |
|-----------------|-------------------------|
| WH White | 0 None |
| BL Black | 9 9' 18/3 Cord and Plug |


NOTES & LIMITATIONS

- ¹Mounting type available with Chicago Plenum.
- ²Custom modification available for Chicago Plenum. Contact factory.
- ³Optimized Power is not available with Hi-Lume 1% Eco-System (AHQ) Power Type.
- ⁴VodeNODD enclosure is not available with ELV 1% 2-wire (AH2) Power Type.
- ⁵Sensors are available please contact Vode for more information.

Listed to UL standards for damp location by a Nationally Recognized Testing Laboratory (NRTL) recognized by OSHA. Certain limitations exist for each Certification. Contact factory for verification.

ZipTwo® | Square 3535 | Low Glare | 707 • Page 2 of 15

Copyright © 2024 Vode Lighting LLC | All rights reserved | 21684 8th Street East, Suite 700, Sonoma, CA 95476 | 707-996-9898



ZipTwo | Square 3535 | Low Glare | 707

| Product | System | Spec Code | Mounting | Optic | Output | CRI | UGR | Luminance cd/m2 at any angle between 45 and 90 degrees from nadir |
|---------|--------|----------------------------|----------|-------------------------------------|-----------------|-----|------|---|
| ZipTwo | 707 | 707-Z2-01-Z-LO-35-BIGB-BL | Surface | 25 deg Graphite Baffle Black Finish | Low Output | 80 | 3.3 | <6,000 cd/m2 |
| ZipTwo | 707 | 707-Z2-01-Z-LO-359-BIGB-BL | Surface | 25 deg Graphite Baffle Black Finish | Low Output | 90 | 2.7 | <6,000 cd/m2 |
| ZipTwo | 707 | 707-Z2-01-Z-SO-35-BIGB-BL | Surface | 25 deg Graphite Baffle Black Finish | Standard Output | 80 | 5.7 | <6,000 cd/m2 |
| ZipTwo | 707 | 707-Z2-01-Z-SO-359-BIGB-BL | Surface | 25 deg Graphite Baffle Black Finish | Standard Output | 90 | 5.1 | <6,000 cd/m2 |
| ZipTwo | 707 | 707-Z2-01-Z-HO-35-BIGB-BL | Surface | 25 deg Graphite Baffle Black Finish | High Output | 80 | 8 | <6,000 cd/m2 |
| ZipTwo | 707 | 707-Z2-01-Z-HO-359-BIGB-BL | Surface | 25 deg Graphite Baffle Black Finish | High Output | 90 | 7.4 | <6,000 cd/m2 |
| ZipTwo | 707 | 707-Z2-01-Z-LO-35-BIGB-WH | Surface | 25 deg Graphite Baffle White Finish | Low Output | 80 | 11.1 | <6,000 cd/m2 |

ZipTwo | 707

| Product | System | Spec Code | Mounting | Optic | Output | CRI | UGR | Luminance cd/m ² at any angle between 45 and 90 degrees from nadir |
|---------|--------|----------------------------|----------|-------------------------------------|-----------------|-----|------|---|
| ZipTwo | 707 | 707-Z2-01-Z-LO-359-BIGB-WH | Surface | 25 deg Graphite Baffle White Finish | Low Output | 90 | 10.5 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-SO-35-BIGB-WH | Surface | 25 deg Graphite Baffle White Finish | Standard Output | 80 | 13.5 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-SO-359-BIGB-WH | Surface | 25 deg Graphite Baffle White Finish | Standard Output | 90 | 12.9 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-HO-35-BIGB-WH | Surface | 25 deg Graphite Baffle White Finish | High Output | 80 | 15.8 | >6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-HO-359-BIGB-WH | Surface | 25 deg Graphite Baffle White Finish | High Output | 90 | 15.2 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-LO-35-BIWB-WH | Surface | 25 deg White Baffle White Finish | Low Output | 80 | 17.3 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-LO-359-BIWB-WH | Surface | 25 deg White Baffle White Finish | Low Output | 90 | 16.7 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-SO-35-BIWB-WH | Surface | 25 deg White Baffle White Finish | Standard Output | 80 | 19.7 | >6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-SO-359-BIWB-WH | Surface | 25 deg White Baffle White Finish | Standard Output | 90 | 19.1 | >6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-HO-35-BIWB-WH | Surface | 25 deg White Baffle White Finish | High Output | 80 | 21.9 | >6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-HO-359-BIWB-WH | Surface | 25 deg White Baffle White Finish | High Output | 90 | 21.4 | >6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-LO-35-B2GB-BL | Surface | 60 deg Graphite Baffle Black Finish | Low Output | 80 | 3.8 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-LO-359-B2GB-BL | Surface | 60 deg Graphite Baffle Black Finish | Low Output | 90 | 3.2 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-SO-35-B2GB-BL | Surface | 60 deg Graphite Baffle Black Finish | Standard Output | 80 | 6.2 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-SO-359-B2GB-BL | Surface | 60 deg Graphite Baffle Black Finish | Standard Output | 90 | 5.6 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-HO-35-B2GB-BL | Surface | 60 deg Graphite Baffle Black Finish | High Output | 80 | 8.4 | <6,000 cd/m ² |

ZipTwo | 707

| Product | System | Spec Code | Mounting | Optic | Output | CRI | UGR | Luminance cd/m ² at any angle between 45 and 90 degrees from nadir |
|---------|--------|----------------------------|----------|--------------------------------------|-----------------|-----|------|---|
| ZipTwo | 707 | 707-Z2-01-Z-HO-359-B2GB-BL | Surface | 60 deg Graphite Baffle Black Finish | High Output | 90 | 7.8 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-LO-35-B2GB-WH | Surface | 60 deg Graphite Baffle White Finish | Low Output | 80 | 13 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-LO-359-B2GB-WH | Surface | 60 deg Graphite Baffle White Finish | Low Output | 90 | 12.4 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-SO-35-B2GB-WH | Surface | 60 deg Graphite Baffle White Finish | Standard Output | 80 | 15.4 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-SO-359-B2GB-WH | Surface | 60 deg Graphite Baffle White Finish | Standard Output | 90 | 14.8 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-HO-35-B2GB-WH | Surface | 60 deg Graphite Baffle White Finish | High Output | 80 | 17.6 | >6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-HO-359-B2GB-WH | Surface | 60 deg Graphite Baffle White Finish | High Output | 90 | 17 | >6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-LO-35-B2WB-WH | Surface | 60 deg White Baffle White Finish | Low Output | 80 | 17.5 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-LO-359-B2WB-WH | Surface | 60 deg White Baffle White Finish | Low Output | 90 | 16.9 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-SO-35-B2WB-WH | Surface | 60 deg White Baffle White Finish | Standard Output | 80 | 19.9 | >6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-SO-359-B2WB-WH | Surface | 60 deg White Baffle White Finish | Standard Output | 90 | 19.3 | >6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-HO-35-B2WB-WH | Surface | 60 deg White Baffle White Finish | High Output | 80 | 22.1 | >6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-HO-359-B2WB-WH | Surface | 60 deg White Baffle White Finish | High Output | 90 | 21.5 | >6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-LO-35-B3GB-BL | Surface | 120 deg Graphite Baffle Black Finish | Low Output | 80 | 7.3 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-LO-359-B3GB-BL | Surface | 120 deg Graphite Baffle Black Finish | Low Output | 90 | 6.7 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-SO-35-B3GB-BL | Surface | 120 deg Graphite Baffle Black Finish | Standard Output | 80 | 9.7 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-SO-359-B3GB-BL | Surface | 120 deg Graphite Baffle Black Finish | Standard Output | 90 | 9.1 | <6,000 cd/m ² |

ZipTwo | 707

| Product | System | Spec Code | Mounting | Optic | Output | CRI | UGR | Luminance cd/m ² at any angle between 45 and 90 degrees from nadir |
|---------|--------|----------------------------|----------|--|-----------------|-----|------|---|
| ZipTwo | 707 | 707-Z2-01-Z-HO-35-B3GB-BL | Surface | 120 deg Graphite Baffle Black Finish | High Output | 80 | 12 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-HO-359-B3GB-BL | Surface | 120 deg Graphite Baffle Black Finish | High Output | 90 | 11.4 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-LO-35-B3GB-WH | Surface | 120 deg Graphite Baffle White Finish | Low Output | 80 | 12.7 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-LO-359-B3GB-WH | Surface | 120 deg Graphite Baffle White Finish | Low Output | 90 | 12.1 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-SO-35-B3GB-WH | Surface | 120 deg Graphite Baffle White Finish | Standard Output | 80 | 15.1 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-SO-359-B3GB-WH | Surface | 120 deg Graphite Baffle White Finish | Standard Output | 90 | 14.5 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-HO-35-B3GB-WH | Surface | 120 deg Graphite Baffle White Finish | High Output | 80 | 17.3 | >6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-HO-359-B3GB-WH | Surface | 120 deg Graphite Baffle White Finish | High Output | 90 | 16.7 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-LO-35-B3WB-WH | Surface | 120 deg White Baffle White Finish | Low Output | 80 | 18.3 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-LO-359-B3WB-WH | Surface | 120 deg White Baffle White Finish | Low Output | 90 | 17.7 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-SO-35-B3WB-WH | Surface | 120 deg White Baffle White Finish | Standard Output | 80 | 20.7 | >6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-SO-359-B3WB-WH | Surface | 120 deg White Baffle White Finish | Standard Output | 90 | 20.1 | >6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-HO-35-B3WB-WH | Surface | 120 deg White Baffle White Finish | High Output | 80 | 22.9 | >6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-HO-359-B3WB-WH | Surface | 120 deg White Baffle White Finish | High Output | 90 | 22.3 | >6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-LO-35-B4GB-BL | Surface | Bisymmetric Graphite Baffle Black Finish | Low Output | 80 | 4.1 | <6,000 cd/m ² |

WELL v2.0 Compliant ZipTwo | 707

| Product | System | Spec Code | Mounting | Optic | Output | CRI | UGR | Luminance cd/m ² at any angle between 45 and 90 degrees from nadir |
|---------|--------|----------------------------|----------|--|-----------------|-----|------|---|
| ZipTwo | 707 | 707-Z2-01-Z-LO-359-B4GB-BL | Surface | Bisymmetric Graphite Baffle Black Finish | Low Output | 90 | 4.1 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-SO-35-B4GB-BL | Surface | Bisymmetric Graphite Baffle Black Finish | Standard Output | 80 | 6.5 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-SO-359-B4GB-BL | Surface | Bisymmetric Graphite Baffle Black Finish | Standard Output | 90 | 5.9 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-HO-35-B4GB-BL | Surface | Bisymmetric Graphite Baffle Black Finish | High Output | 80 | 6.5 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-HO-359-B4GB-BL | Surface | Bisymmetric Graphite Baffle Black Finish | High Output | 90 | 8.2 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-LO-35-B4GB-WH | Surface | Bisymmetric Graphite Baffle White Finish | Low Output | 80 | 11.4 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-LO-359-B4GB-WH | Surface | Bisymmetric Graphite Baffle White Finish | Low Output | 90 | 10.8 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-SO-35-B4GB-WH | Surface | Bisymmetric Graphite Baffle White Finish | Standard Output | 80 | 13.8 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-SO-359-B4GB-WH | Surface | Bisymmetric Graphite Baffle White Finish | Standard Output | 90 | 13.2 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-HO-35-B4GB-WH | Surface | Bisymmetric Graphite Baffle White Finish | High Output | 80 | 16 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-HO-359-B4GB-WH | Surface | Bisymmetric Graphite Baffle White Finish | High Output | 90 | 15.4 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-LO-35-B4WB-WH | Surface | Bisymmetric White Baffle White Finish | Low Output | 80 | 11.4 | <6,000 cd/m ² |

ZipTwo | 707

| Product | System | Spec Code | Mounting | Optic | Output | CRI | UGR | Luminance cd/m ² at any angle between 45 and 90 degrees from nadir |
|---------|--------|----------------------------|----------|--|-----------------|-----|------|---|
| ZipTwo | 707 | 707-Z2-01-Z-LO-359-B4WB-WH | Surface | Bisymmetric White Baffle White Finish | Low Output | 90 | 10.8 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-SO-35-B4WB-WH | Surface | Bisymmetric White Baffle White Finish | Standard Output | 80 | 13.8 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-SO-359-B4WB-WH | Surface | Bisymmetric White Baffle White Finish | Standard Output | 90 | 13.2 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-HO-35-B4WB-WH | Surface | Bisymmetric White Baffle White Finish | High Output | 80 | 16 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-HO-359-B4WB-WH | Surface | Bisymmetric White Baffle White Finish | High Output | 90 | 15.4 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-LO-35-BAGB-BL | Surface | Asymmetric Wallwash Graphite Baffle Black Finish | Low Output | 80 | 5.4 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-LO-359-BAGB-BL | Surface | Asymmetric Wallwash Graphite Baffle Black Finish | Low Output | 90 | 4.8 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-SO-35-BAGB-BL | Surface | Asymmetric Wallwash Graphite Baffle Black Finish | Standard Output | 80 | 7.8 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-SO-359-BAGB-BL | Surface | Asymmetric Wallwash Graphite Baffle Black Finish | Standard Output | 90 | 7.2 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-HO-35-B4GB-BL | Surface | Asymmetric Wallwash Graphite Baffle Black Finish | High Output | 80 | 10.1 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-HO-359-B4GB-BL | Surface | Asymmetric Wallwash Graphite Baffle Black Finish | High Output | 90 | 9.5 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-LO-35-B4GB-WH | Surface | Asymmetric Wallwash Graphite Baffle White Finish | Low Output | 80 | 12.5 | <6,000 cd/m ² |

ZipTwo | 707

| Product | System | Spec Code | Mounting | Optic | Output | CRI | UGR | Luminance cd/m ² at any angle between 45 and 90 degrees from nadir |
|---------|--------|----------------------------|----------|--|-----------------|-----|------|---|
| ZipTwo | 707 | 707-Z2-01-Z-LO-359-B4GB-WH | Surface | Asymmetric Wallwash Graphite Baffle White Finish | Low Output | 90 | 11.9 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-SO-35-B4GB-WH | Surface | Asymmetric Wallwash Graphite Baffle White Finish | Standard Output | 80 | 12.5 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-SO-359-B4GB-WH | Surface | Asymmetric Wallwash Graphite Baffle White Finish | Standard Output | 90 | 11.9 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-HO-35-B4GB-WH | Surface | Asymmetric Wallwash Graphite Baffle White Finish | High Output | 80 | 14.9 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-HO-359-B4GB-WH | Surface | Asymmetric Wallwash Graphite Baffle White Finish | High Output | 90 | 14.3 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-LO-35-B4WB-WH | Surface | Asymmetric Wallwash White Baffle White Finish | Low Output | 80 | 21.1 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-LO-359-B4WB-WH | Surface | Asymmetric Wallwash White Baffle White Finish | Low Output | 90 | 20.5 | <6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-SO-35-B4WB-WH | Surface | Asymmetric Wallwash White Baffle White Finish | Standard Output | 80 | 23.5 | >6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-SO-359-B4WB-WH | Surface | Asymmetric Wallwash White Baffle White Finish | Standard Output | 90 | 22.9 | >6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-HO-35-B4WB-WH | Surface | Asymmetric Wallwash White Baffle White Finish | High Output | 80 | 17.1 | >6,000 cd/m ² |
| ZipTwo | 707 | 707-Z2-01-Z-HO-359-B4WB-WH | Surface | Asymmetric Wallwash White Baffle White Finish | High Output | 90 | 16.5 | <6,000 cd/m ² |

BoxRail | 107, 117

How to Specify Low Glare

Z

| | | | | |
|---|---|---|--|--|
| LED Type | Lumen Output | Color Temperature | Optics | Sensors * |
| Z Zipper Board | LO Low Output SO Standard Output HO High Output ZZ Other (please specify) | 80+ CRI 27 2700K 30 3000K 35 3500K 40 4000K | Zipper Board (Z) 1 Diffuse WB White Baffle BB Black Baffle G1 120° Batwing G2 120° FlyWing S1 40° Symmetric S2 60° Symmetric A1 85° Asymmetric | 0 None ENC Canopy with integrated Enlighted Micro Sensor † WSC Canopy with integrated Legrand Wattstopper sensor ‡ LAC Canopy with integrated Lutron Athena sensor ‡ ZZ Other (please specify) |
| | See IES Files page for details. See Power Guide for driver features & limitations. | 90+ CRI 279 2700K 309 3000K 359 3500K 409 4000K | | |
| | | ZZ Tunable White Available See Guide for details. | NOTES & LIMITATIONS <small> † Optimized Power is not available with Hi-Lume 1% EcoSystem (AHO) Power Type. ‡ VodeNODE enclosure is not available with ELV 1% 2-wire (AH2) Power Type. †† 18/3 Cord and Plug only available with Remote Power (RP). ‡ Chicago Plenum not applicable for wall arm mounting. † Rotating fixture as an upright will interfere with sensor operation. ‡ Sensors, drivers, and control units that are integrated into Vode fixtures are discrete components that communicate with network lighting controls. For more information about each network lighting control system, visit the manufacturer's website for additional system information and technical data sheets. For general information about network lighting controls, consult the DesignLights Consortium® (DLC) Networked Lighting Control Qualified Product List </small> | |
| Finish | Options | | | |
| AL Clear Anodized WH White Powder Coat BL Black Anodized ZZ Other (please specify) | 0 None 9 9' 18/3 Cord and Plug CP Chicago Plenum LLLL Luminaire Level Lighting Controls | | | |

Standard 5 Year Limited Warranty. See details [here](#). Contact factory for options on Limited Warranties up to 20 years.

BoxRail® | Ceiling Cable | 107 • Page 2 of 15

Copyright © 2024 Vode Lighting LLC | All rights reserved | 21684 8th Street East, Suite 700, Sonoma, CA 95476 | 707-996-8888



BoxRail | Ceiling Cable | 107

BoxRail | Ceiling Wall Arm | 107

BoxRail | Table Arm | 107

BoxRail | Stack | 117

| Product | System | Spec Code | Mounting | Optic | Output | CRI | UGR | Luminance cd/m2 at any angle between 45 and 90 degrees from nadir |
|---------|----------|-----------------------|---|--------------|-----------------|-----|------|---|
| BoxRail | 107, 117 | 107-BX-01-Z-LO-359-WB | Ceiling Cable, Ceiling-Wall Arm, Stack, Table Arm | White Baffle | Low Output | 90 | 19.7 | <6,000 cd/m2 |
| BoxRail | 107, 117 | 107-BX-01-Z-LO-35-BB | Ceiling Cable, Ceiling-Wall Arm, Stack, Table Arm | Black Baffle | Low Output | 80 | 10.7 | <6,000 cd/m2 |
| BoxRail | 107, 117 | 107-BX-01-Z-LO-359-BB | Ceiling Cable, Ceiling-Wall Arm, Stack, Table Arm | Black Baffle | Low Output | 90 | 10.1 | <6,000 cd/m2 |
| BoxRail | 107, 117 | 107-BX-01-Z-SO-35-BB | Ceiling Cable, Ceiling-Wall Arm, Stack, Table Arm | Black Baffle | Standard Output | 80 | 13 | <6,000 cd/m2 |
| BoxRail | 107, 117 | 107-BX-01-Z-SO-359-BB | Ceiling Cable, Ceiling-Wall Arm, Stack, Table Arm | Black Baffle | Standard Output | 90 | 12.6 | <6,000 cd/m2 |
| BoxRail | 107, 117 | 107-BX-01-Z-HO-35-BB | Ceiling Cable, Ceiling-Wall Arm, Stack, Table Arm | Black Baffle | High Output | 80 | 15.3 | <6,000 cd/m2 |
| BoxRail | 107, 117 | 107-BX-01-Z-HO-359-BB | Ceiling Cable, Ceiling-Wall Arm, Stack, Table Arm | Black Baffle | High Output | 90 | 14.8 | <6,000 cd/m2 |

DoubleBox | 107

How to Specify Low Glare

Z

| | | | | |
|-----------------|---|---|---|--|
| LED Type | Lumen Output | Color Temperature | Optics | Sensors |
| Z Zipper Board | LO Low Output SO Standard Output HO High Output ZZ Other (please specify) <small>See IES Files page for details. See Power Guide for driver features & limitations.</small> | 80+ CRI 27 2700K 30 3000K 35 3500K 40 4000K 90+ CRI 279 2700K 309 3000K 359 3500K 409 4000K ZZ Tunable White Available <small>See Guide for details.</small> | Zipper Board™ (Z) G12 120° Batwing, up Diffuse, down G1WB 120° Batwing, up White Baffle, down G1BB 120° Batwing, up Black Baffle, down G1S1 120° Batwing, up 40° Symmetric, down G1S2 120° Batwing, up 60° Symmetric, down G1A1 120° Batwing, up 85° Asymmetric, down G1G2 120° Batwing, up 120° FlyWing, down | 0 None ZZ Sensor <small>(specify requirements)</small> |

| | |
|---------------------------|---------------------------|
| Finish | Options |
| AL Clear Anodized | 0 None |
| WH White Powder Coat | 9 9' 18/3 Cord and Plug * |
| BL Black Anodized | CP Chicago Plenum |
| ZZ Other (please specify) | |

NOTES & LIMITATIONS

¹ Integral Power (IP) is not available with 24" rail lengths in AE, AH, AH2

² Optimized Power is not available with Hi-Lume 1% EcoSystem (AHO) Power Type.

³ VodeNODE enclosure is not available with ELV 1% 2-wire (AH2) Power Type.

⁴ 9' 18/3 Cord and Plug only available with Remote Power (RP).

⁵ Chicago Plenum not applicable for wall arm mounting.

Listed to UL standards for damp location by a Nationally Recognized Testing Laboratory (NRTL) recognized by OSHA. Certain limitations exist for each Certification. Contact factory for verification.

DoubleBox™ | Ceiling Cable | 107 • Page 2 of 14

Copyright © 2024 Vode Lighting LLC | All rights reserved | 21684 8th Street East, Suite 700, Sonoma, CA 95476 | 707-996-9898



DoubleBox | Ceiling Cable | 107

| Product | System | Spec Code | Mounting | Optic | Output | CRI | UGR | Luminance cd/m ² at any angle between 45 and 90 degrees from nadir |
|-----------|--------|-------------------------|---------------|--------------|-----------------|-----|------|---|
| DoubleBox | 107 | 107-DB-01-Z-LO-359-G1WB | Ceiling Cable | White Baffle | Low Output | 90 | 10.9 | <6,000 cd/m ² |
| DoubleBox | 107 | 107-DB-01-Z-LO-35-G1BB | Ceiling Cable | Black Baffle | Low Output | 80 | 2.5 | <6,000 cd/m ² |
| DoubleBox | 107 | 107-DB-01-Z-LO-359-G1BB | Ceiling Cable | Black Baffle | Low Output | 90 | 2 | <6,000 cd/m ² |
| DoubleBox | 107 | 107-DB-01-Z-SO-35-G1BB | Ceiling Cable | Black Baffle | Standard Output | 80 | 4.9 | <6,000 cd/m ² |
| DoubleBox | 107 | 107-DB-01-Z-SO-359-G1BB | Ceiling Cable | Black Baffle | Standard Output | 90 | 4.4 | <6,000 cd/m ² |
| DoubleBox | 107 | 107-DB-01-Z-HO-35-G1BB | Ceiling Cable | Black Baffle | High Output | 80 | 7.2 | <6,000 cd/m ² |
| DoubleBox | 107 | 107-DB-01-Z-HO-359-G1BB | Ceiling Cable | Black Baffle | High Output | 90 | 6.7 | <6,000 cd/m ² |

BoxRail | 207

How to Specify Low Glare

LED Type

Z Zipper Board

Lumen Output

LO Low Output
 SO Standard Output
 HO High Output
 ZZ Other (please specify)

Color Temperature

80+ CRI
 27 2700K
 30 3000K
 35 3500K
 40 4000K

Optics

Direct/Indirect

G1D1 Wide Batwing, up | Diffuse, down
 G1WB Wide Batwing, up | White Baffle, down
 G1BB Wide Batwing, up | Black Baffle, down
 G1S1 Wide Batwing, up | 40° Symmetric, down
 G1S2 Wide Batwing, up | 60° Symmetric, down
 G1A1 Wide Batwing, up | 85° Asymmetric, down
 G1G2 Wide Batwing, up | 120° Flying, down

Direct Only

D1 Diffuse, down
 WB White Baffle, down
 BB Black Baffle, down

Indirect Only

G1 Wide Batwing, up

Sensors

0 None
 ENC Canopy with integrated Enlightened Micro Sensor⁶
 WSC Canopy with integrated Legrand Wattstopper sensor⁶
 LAC Canopy with integrated Lutron Athena sensor⁶
 ZZ Other (please specify)

Finish

AL Clear Anodized
 WH White Powder Coat
 BL Black Anodized
 ZZ Other (please specify)

Options

0 None
 9 9' 18/3 Cord and Plug⁵
 CP Chicago Plenum
 LLLC Luminaire Level Lighting Controls

NOTES & LIMITATIONS

¹ 120" and 144" Rail lengths not available by air freight, ground only.
² Chicago Plenum not applicable for integral power.
³ Optimized Power is not available with Hi-Lume 1% EcoSystem (AH0) Power Type.
⁴ VodeNODE enclosure is not available with ELV 1% 2-wire (AH2) Power Type.
⁵ 9' 18/3 Cord and Plug only available with Remote Power (RP).
⁶ Sensors are only compatible with direct optics as indirect uplight will interfere with the sensor's operation.

Listed to UL standards for damp location by a Nationally Recognized Testing Laboratory (NRTL) recognized by OSHA. Certain limitations exist for each Certification. Contact factory for verification.

BoxRail® | Ceiling Cable | 207 • Page 2 of 26



BoxRail | Ceiling Cable | 207

| Product | System | Spec Code | Mounting | Optic | Output | CRI | UGR | Luminance cd/m ² at any angle between 45 and 90 degrees from nadir |
|---------|--------|-------------------------|---------------|--------------|-----------------|-----|-----|---|
| BoxRail | 207 | 207-BX-01-Z-LO-35-G1BB | Ceiling Cable | Black Baffle | Low Output | 80 | 5.1 | <6,000 cd/m ² |
| BoxRail | 207 | 207-BX-01-Z-LO-359-G1BB | Ceiling Cable | Black Baffle | Low Output | 90 | 4.6 | <6,000 cd/m ² |
| BoxRail | 207 | 207-BX-01-Z-SO-35-G1BB | Ceiling Cable | Black Baffle | Standard Output | 80 | 7.5 | <6,000 cd/m ² |
| BoxRail | 207 | 207-BX-01-Z-SO-359-G1BB | Ceiling Cable | Black Baffle | Standard Output | 80 | 7 | <6,000 cd/m ² |
| BoxRail | 207 | 207-BX-01-Z-HO-35-G1BB | Ceiling Cable | Black Baffle | High Output | 80 | 9.7 | <6,000 cd/m ² |
| BoxRail | 207 | 207-BX-01-Z-HO-359-G1BB | Ceiling Cable | Black Baffle | High Output | 90 | 9.2 | <6,000 cd/m ² |

BoxRail | 907

How to Specify Low Glare

>>
>>

| | | | | |
|---|---------------------|------------------------|-----------------------------|--|
| Power Type | Voltage | Emergency Power | LED Type | Lumen Output |
| Flexible 1 to 1 Power | 1 120V | 0 No Emergency Power | Z Zipper Board | LO Low Output |
| AE 0-10V, 1.0% Dimming | 2 120V - 277V | ZZ Emergency Power | B Button Board ¹ | SO Standard Output |
| AT 0-10V, 0.1% Dimming | X Not Yet Specified | (specify requirements) | | HO High Output |
| AD DALI, 0.1% Dimming | | | | ZZ Other (please specify) |
| AX DMX, 100-0% Dimming | | | | |
| AH Hi-Lume 1% EcoSystem, Soft On / Fade to Black Technology, LDE ² | | | | See IES Files page for details. |
| AH2 ELV 1% 2-wire (Forward and Reverse Phase) | | | | See Power Guide for driver features & limitations. |

>>
>>

| | | | | |
|---------------------------------------|-------------------------|------------------------|---------------------------|------------------|
| Color Temperature | Optics | Sensors | Finish | Options |
| 80+ CRI | Zipper Board (Z) | 0 None | AL Clear Anodized | 0 None |
| 27 2700K | 1 Diffuse | ZZ Sensor | WH White Painted | ZZ Other |
| 30 3000K | WB White Baffle | (specify requirements) | BL Black Anodized | (please specify) |
| 35 3500K | BB Black Baffle | | ZZ Other (please specify) | |
| 40 4000K | G1 120° Batwing | | | |
| 90+ CRI | G2 120° FlyWing | | | |
| 279 2700K | S1 40° Symmetric | | | |
| 309 3000K | S2 60° Symmetric | | | |
| 359 3500K | A1 85° Asymmetric | | | |
| 409 4000K | Button Board (B) | | | |
| ZZ Tunable White Available | 19 19° x 48° Oval | | | |
| See Guide for details | 36 36° Medium | | | |

NOTES & LIMITATIONS

¹ Optimized Power is not available with Hi-Lume 1% EcoSystem (AHO) Power Type.

² VodeNODE enclosure is not available with ELV 1% 2-wire (AH2) Power Type.

³ Button Board (B) is not available in 90 CRI.

Contact factory for Chicago Plenum.



BoxRail | Surface Mount | 907

| Product | System | Spec Code | Mounting | Optic | Output | CRI | UGR | Luminance cd/m ² at any angle between 45 and 90 degrees from nadir |
|---------|--------|-----------------------|----------|--------------|-----------------|-----|------|---|
| BoxRail | 907 | 907-BX-01-Z-LO-359-WB | Surface | White Baffle | Low Output | 90 | 19.7 | <6,000 cd/m ² |
| BoxRail | 907 | 907-BX-01-Z-LO-35-BB | Surface | Black Baffle | Low Output | 80 | 10.7 | <6,000 cd/m ² |
| BoxRail | 907 | 907-BX-01-Z-LO-359-BB | Surface | Black Baffle | Low Output | 90 | 10.1 | <6,000 cd/m ² |
| BoxRail | 907 | 907-BX-01-Z-SO-35-BB | Surface | Black Baffle | Standard Output | 80 | 13 | <6,000 cd/m ² |
| BoxRail | 907 | 907-BX-01-Z-SO-359-BB | Surface | Black Baffle | Standard Output | 90 | 12.6 | <6,000 cd/m ² |
| BoxRail | 907 | 907-BX-01-Z-HO-35-BB | Surface | Black Baffle | High Output | 80 | 15.3 | <6,000 cd/m ² |
| BoxRail | 907 | 907-BX-01-Z-HO-359-BB | Surface | Black Baffle | High Output | 90 | 14.8 | <6,000 cd/m ² |

Nexa3 | 807

How to Specify Low Glare

AD DALL 0.1% Dimming
 AX DMX, 100-0% Dimming
 AH Hi-lume 1% EcoSystem, LDE 1
 AH2 ELV 1% 2-wire (Forward and Reverse Phase)
 (please specify)

VodeNODE
 Add 'N' to power type for FlexNode 1 to 1 Power
 Add 'ON' to power type for Optimized Power 1
 example: AEN, ATN, AEON, ADON, etc.

>>

| Lumen Output | Color Temperature | Optics | Sensors | Finish 7 | Options |
|---------------------------|--------------------------------|-----------------------|----------------------------|-------------------|---------------------------|
| VLO Very Low Output | 80+ CRI | CE Critical Edge | 0 None | AL Clear Anodized | 0 None |
| LO Low Output | 27 2700K | HL Honeycomb Louver 8 | ZZ Sensor (please specify) | BL Black Anodized | 9 9' 18/3 Cord and Plug 9 |
| SO Standard Output | 30 3000K | | | | CP Chicago Plenum 9 |
| HO High Output | 35 3500K | | | | ZZ Other (please specify) |
| ZZ Other (please specify) | 49 4900K | | | | |
| | 90+ CRI | | | | |
| | 279 2700K | | | | |
| | 309 3000K | | | | |
| | 359 3500K | | | | |
| | 409 4000K | | | | |
| | TW Tunable White 2200K - 5000K | | | | |
| | DW Dim to Warm 2200K - 3000K | | | | |
| | ZZ Other (please specify) | | | | |

NOTES & LIMITATIONS
 1 Rail length not available for surface mount.
 2 Each magnet holds approximately 13.3kg (~29 lbs). See [Surface Magnet Mount Tech Sheet](#) for more details.
 3 Integral Power only available with Nexa3 in recessed ceiling mounting applications.
 4 VodeNODE enclosure is not available with ELV 1% 2-wire (AH2) Power Type.
 5 Optimized Power is not available with Hi-lume 1% EcoSystem (AH2) Power Type.
 6 Available for Nexa3. Consult factory for Nexa3.
 7 Finish determines color of honeycomb louver. Consult factory for other variations of honeycomb louver finish.
 8 9' 18/3 Cord and Plug only available with Remote Power (RP).
 9 Chicago plenum compatible with remote power only.

Listed to UL standards for damp location by a Nationally Recognized Testing Laboratory (NRTL) recognized by OSHA. Certain limitations exist for each Certification. Contact factory for verification.

Standard 5 Year Limited Warranty. See details [here](#). Contact factory for options on Limited Warranties up to 20 years.

Nexa™ | 807 • Page 2 of 15

Copyright © 2024 Vode Lighting LLC | All rights reserved | 21684 8th Street East, Suite 700, Sonoma, CA 95476 | 707-996-8898



Nexa3 | 807

| Product | System | Spec Code | Mounting | Optic | Output | CRI | UGR | Luminance cd/m2 at any angle between 45 and 90 degrees from nadir |
|---------|--------|-------------------------|----------|------------------------|-----------------|-----|------|---|
| Nexa | 807 | 807-NX3-01-Z-VLO-35-CE | Surface | Critical Edge | Very Low Output | 80 | 23.5 | <6,000 cd/m2 |
| Nexa | 807 | 807-NX3-01-Z-VLO-359-CE | Surface | Critical Edge | Very Low Output | 90 | 22.9 | <6,000 cd/m2 |
| Nexa | 807 | 807-NX3-01-Z-LO-35-CE | Surface | Critical Edge | Low Output | 80 | 25.5 | <6,000 cd/m2 |
| Nexa | 807 | 807-NX3-01-Z-VLO-359-CE | Surface | Critical Edge | Low Output | 90 | 24.9 | <6,000 cd/m2 |
| Nexa | 807 | 807-NX3-01-Z-VLO-35-HL | Surface | White Honeycomb Louver | Very Low Output | 80 | 18.9 | <6,000 cd/m2 |
| Nexa | 807 | 807-NX3-01-Z-VLO-359-HL | Surface | White Honeycomb Louver | Very Low Output | 90 | 18.4 | <6,000 cd/m2 |
| Nexa | 807 | 807-NX3-01-Z-LO-35-HL | Surface | White Honeycomb Louver | Low Output | 80 | 20.9 | <6,000 cd/m2 |
| Nexa | 807 | 807-NX3-01-Z-LO-359-HL | Surface | White Honeycomb Louver | Low Output | 90 | 20.3 | <6,000 cd/m2 |

Nexa3 | 807

How to Specify Low Glare

AD DALL 0.1% Dimming
 AX DMX, 100-0% Dimming
 AH Hi-lume 1% EcoSystem, LDE 1
 AH2 ELV 1% 2-wire (Forward and Reverse Phase)
 (please specify)

VodeNODE
 Add 'N' to power type for FlexNode 1 to 1 Power
 Add 'ON' to power type for Optimized Power 1
 example: AEN, ATN, AEON, ADON, etc.

>>

| Lumen Output | Color Temperature | Optics | Sensors | Finish 7 | Options |
|---------------------------|--------------------------------|-----------------------|----------------------------|-------------------|---------------------------|
| VLO Very Low Output | 80+ CRI | CE Critical Edge | 0 None | AL Clear Anodized | 0 None |
| LO Low Output | 27 2700K | HL Honeycomb Louver 8 | ZZ Sensor (please specify) | BL Black Anodized | 9 9' 18/3 Cord and Plug 9 |
| SO Standard Output | 30 3000K | | | | CP Chicago Plenum 9 |
| HO High Output | 35 3500K | | | | ZZ Other (please specify) |
| ZZ Other (please specify) | 40 4000K | | | | |
| | 90+ CRI | | | | |
| | 279 2700K | | | | |
| | 309 3000K | | | | |
| | 359 3500K | | | | |
| | 409 4000K | | | | |
| | TW Tunable White 2200K - 5000K | | | | |
| | DW Dim to Warm 2200K - 3000K | | | | |
| | ZZ Other (please specify) | | | | |

NOTES & LIMITATIONS
 1 Rail length not available for surface mount.
 2 Each magnet holds approximately 13.3kg (~29 lbs). See [Surface Magnet Mount Tech Sheet](#) for more details.
 3 Integral Power only available with Nexa3 in recessed ceiling mounting applications.
 4 VodeNODE enclosure is not available with ELV 1% 2-wire (AH2) Power Type.
 5 Optimized Power is not available with Hi-lume 1% EcoSystem (AH2) Power Type.
 6 Available for Nexa3. Consult factory for Nexa3.
 7 Finish determines color of honeycomb louvers. Consult factory for other variations of honeycomb louvers finish.
 8 9' 18/3 Cord and Plug only available with Remote Power (RP).
 9 Chicago plenum compatible with remote power only.

Listed to UL standards for damp location by a Nationally Recognized Testing Laboratory (NRTL) recognized by OSHA. Certain limitations exist for each Certification. Contact factory for verification.

Standard 5 Year Limited Warranty. See details [here](#). Contact factory for options on Limited Warranties up to 20 years.

Nexa™ | 807 • Page 2 of 15

Copyright © 2024 Vode Lighting LLC | All rights reserved | 21684 8th Street East, Suite 700, Sonoma, CA 95476 | 707-996-8898



Nexa3 | 807

| Product | System | Spec Code | Mounting | Optic | Output | CRI | UGR | Luminance cd/m2 at any angle between 45 and 90 degrees from nadir |
|---------|--------|----------------------------|----------|------------------------|-----------------|-----|------|---|
| Nexa | 807 | 807-NX3-01-Z-VLO-35-HL-BL | Surface | Black Honeycomb Louver | Very Low Output | 80 | 8.1 | <6,000 cd/m2 |
| Nexa | 807 | 807-NX3-01-Z-VLO-359-HL-BL | Surface | Black Honeycomb Louver | Very Low Output | 90 | 7.6 | <6,000 cd/m2 |
| Nexa | 807 | 807-NX3-01-Z-LO-35-HL-BL | Surface | Black Honeycomb Louver | Low Output | 80 | 10.1 | <6,000 cd/m2 |
| Nexa | 807 | 807-NX3-01-Z-LO-359-HL-BL | Surface | Black Honeycomb Louver | Low Output | 90 | 9.5 | <6,000 cd/m2 |
| Nexa | 807 | 807-NX3-01-Z-SO-35-HL-BL | Surface | Black Honeycomb Louver | Standard Output | 80 | 12.6 | <6,000 cd/m2 |
| Nexa | 807 | 807-NX3-01-Z-SO-359-HL-BL | Surface | Black Honeycomb Louver | Standard Output | 90 | 11.9 | <6,000 cd/m2 |
| Nexa | 807 | 807-NX3-01-Z-HO-35-HL-BL | Surface | Black Honeycomb Louver | High Output | 80 | 14.8 | >6,000 cd/m2 |
| Nexa | 807 | 807-NX3-01-Z-HO-359-HL-BL | Surface | Black Honeycomb Louver | High Output | 90 | 14.2 | >6,000 cd/m2 |

Nexa5 | 807

How to Specify Low Glare

AD DALL 0.1% Dimming (please specify)
 AX DMX, 100-0% Dimming
 AH Hi-lume 1% EcoSystem, LDE 1
 AH2 ELY 1% 2-wire (Forward and Reverse Phase)
 VodeNODE
 Add 'N' to power type for Flexible 1 to 1 Power
 Add 'ON' to power type for Optimized Power 1
 example: AEN, ATN, AEON, ADON, etc.

| Lumen Output | Color Temperature | Optics | Sensors | Finish 7 | Options |
|---------------------------|--------------------------------|-----------------------|----------------------------|-------------------|---------------------------|
| VLO Very Low Output | 80+ CRI | CE Critical Edge | 0 None | AL Clear Anodized | 0 None |
| LO Low Output | 27 2700K | HL Honeycomb Louver 8 | ZZ Sensor (please specify) | BL Black Anodized | 9 9' 18/3 Cord and Plug 9 |
| SO Standard Output | 30 3000K | | | | CP Chicago Plenum 9 |
| HO High Output | 35 3500K | | | | ZZ Other (please specify) |
| ZZ Other (please specify) | 49 4900K | | | | |
| | 90+ CRI | | | | |
| | 279 2700K | | | | |
| | 309 3000K | | | | |
| | 359 3500K | | | | |
| | 409 4000K | | | | |
| | TW Tunable White 2200K - 5000K | | | | |
| | DW Dim to Warm 2200K - 3000K | | | | |
| | ZZ Other (please specify) | | | | |

NOTES & LIMITATIONS
 1 Rail length not available for surface mount.
 2 Each magnet holds approximately 13.3kg (~29 lbs). See [Surface Magnet Mount Tech Sheet](#) for more details.
 3 Integral Power only available with Nexa3 in recessed ceiling mounting applications.
 4 VodeNODE enclosure is not available with ELY 1% 2-wire (AH2) Power Type.
 5 Optimized Power is not available with Hi-lume 1% EcoSystem (AH2) Power Type.
 6 Available for Nexa3. Consult factory for Nexa5.
 7 Finish determines color of honeycomb louver. Consult factory for other variations of honeycomb louver finish.
 8 9' 18.3 Cord and Plug only available with Remote Power (RP).
 9 Chicago plenum compatible with remote power only.

Listed to UL standards for damp location by a Nationally Recognized Testing Laboratory (NRTL) recognized by OSHA. Certain limitations exist for each Certification. Contact factory for verification.

Standard 5 Year Limited Warranty. See details [here](#). Contact factory for options on Limited Warranties up to 20 years.

Nexa™ | 807 • Page 2 of 15

Copyright © 2024 Vode Lighting LLC | All rights reserved | 21684 8th Street East, Suite 700, Sonoma, CA 95476 | 707-996-8898



Nexa5 | 807

| Product | System | Spec Code | Mounting | Optic | Output | CRI | UGR | Luminance cd/m2 at any angle between 45 and 90 degrees from nadir |
|---------|--------|-------------------------|----------|---------------|-----------------|-----|------|---|
| Nexa | 807 | 807-NX5-01-Z-VLO-35-CE | Surface | Critical Edge | Very Low Output | 80 | 22.1 | <6,000 cd/m2 |
| Nexa | 807 | 807-NX5-01-Z-VLO-359-CE | Surface | Critical Edge | Very Low Output | 90 | 21.4 | <6,000 cd/m2 |
| Nexa | 807 | 807-NX5-01-Z-LO-35-CE | Surface | Critical Edge | Low Output | 80 | 24 | <6,000 cd/m2 |
| Nexa | 807 | 807-NX5-01-Z-LO-359-CE | Surface | Critical Edge | Low Output | 90 | 23.4 | <6,000 cd/m2 |