

IES Report

WingRail® | 107 | Clear with EdgeSoft™ | 80 CRI | LO

107-WG-XX-4-48-XX-XX-XX-XX-X-X-Z-LO-35-C1-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	91	94	96	97
Total Lumens, 4' rail length (1219mm)	1349	1392	1420	1449
Lumens per foot (305mm)	337	348	355	362
Input Power (W), 4' rail length (1219mm)	15.0	15.0	15.0	15.0
Watts per foot (305mm)	3.8	3.8	3.8	3.8
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES INDOOR REPORT
PHOTOMETRIC FILENAME : VODE_107_WG_LO_35_C1.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002
[TEST] L071704217 (SOURCE REPORT FOR REFERENCE)
[TESTLAB] REPORT BASED ON DATA PRODUCED BY NVLAP ACCREDITED LAB
[ISSUEDATE] 11/1/2017
[MANUFAC] Vode Lighting
[LUMCAT] 107-WG-48-Z-LO-35-C1
[LUMINAIRE] WingRail LED, 48", 3500K, 80 CRI, zipper board,
[MORE] clear lens w/edge softening, low output
[TEST PROCEDURE] IESNA:LM-79-08

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	1417
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	95
Total Luminaire Watts	14.95
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.66
Spacing Criterion (90-270)	1.24
Spacing Criterion (Diagonal)	1.30
Basic Luminous Shape	Rectangular
Luminous Length (0-180)	0.13 ft
Luminous Width (90-270)	3.83 ft
Luminous Height	0.00 ft

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	17535	15625	10524
55	17729	15707	9353
65	15770	14322	7840
75	12555	11866	6105
85	8626	9065	3801

CANDELA TABULATION

	<u>0</u>	<u>5</u>	<u>10</u>	<u>15</u>	<u>20</u>	<u>25</u>	<u>30</u>	<u>35</u>	<u>40</u>	<u>45</u>
0	551.06	551.06	551.06	551.06	551.06	551.06	551.06	551.06	551.06	551.06
5	575.84	575.84	575.25	574.66	574.07	573.48	572.30	571.12	569.94	568.17
10	598.26	597.67	597.08	596.49	594.72	593.54	591.18	588.82	585.87	582.92
15	613.01	613.01	611.83	610.65	608.88	605.93	602.98	599.44	595.31	591.18
20	621.86	621.27	620.09	618.32	615.96	612.42	608.88	604.16	598.85	592.95
25	625.40	624.81	623.04	620.68	617.73	613.60	608.29	602.98	595.90	588.82
30	623.04	622.45	621.27	618.32	614.19	608.88	603.57	596.49	588.23	579.38
35	615.37	614.78	613.01	609.47	604.75	599.44	592.36	584.10	574.66	564.04
40	600.03	599.44	597.67	593.54	588.82	581.74	574.07	564.63	554.01	542.21
45	574.07	573.48	571.12	566.99	561.68	554.01	545.75	535.72	523.92	511.53
50	532.18	531.00	529.23	525.10	519.79	513.30	505.04	495.01	483.21	470.23
55	470.82	470.23	468.46	466.10	461.38	455.48	448.99	439.55	428.93	417.13
60	394.12	394.12	392.35	390.58	387.04	382.91	377.60	371.11	362.26	352.23
65	308.57	308.57	307.98	306.80	305.03	302.08	298.54	293.82	287.92	280.25
70	225.38	224.79	224.79	224.20	223.61	221.84	220.07	217.12	213.58	208.27
75	150.45	150.45	150.45	150.45	150.45	149.86	148.68	147.50	145.14	142.19
80	85.55	85.55	85.55	86.14	86.14	86.73	86.14	86.14	84.96	83.19
85	34.81	34.81	34.81	35.40	35.99	35.99	36.58	36.58	36.58	36.58
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

Vert. Horizontal Angles
 Angles

	<u>50</u>	<u>55</u>	<u>60</u>	<u>65</u>	<u>70</u>	<u>75</u>	<u>80</u>	<u>85</u>	<u>90</u>	<u>95</u>
0	551.06	551.06	551.06	551.06	551.06	551.06	551.06	551.06	551.06	551.06
5	566.40	564.63	562.86	560.50	558.73	556.37	554.01	551.65	549.29	546.93
10	579.38	575.25	571.12	566.99	562.27	557.55	552.24	547.52	542.21	536.90
15	585.87	579.97	573.48	566.99	560.50	553.42	545.75	537.49	529.82	520.97
20	585.87	578.79	570.53	561.68	552.83	543.39	533.36	522.74	511.53	499.73
25	580.56	571.71	561.68	551.06	539.85	528.05	515.66	502.09	488.52	473.18
30	569.35	558.73	546.93	534.54	521.56	507.40	492.65	476.72	459.61	441.32
35	552.24	539.85	526.87	512.12	497.37	481.44	463.74	446.04	425.98	404.74
40	528.64	515.07	499.73	484.39	467.28	449.58	430.11	410.05	387.63	363.44
45	497.37	482.03	465.51	448.40	429.52	410.64	389.99	368.16	344.56	318.60
50	455.48	439.55	422.44	404.15	385.27	365.80	343.97	322.14	297.95	271.40
55	402.97	388.22	371.11	352.82	333.94	314.47	293.82	271.99	248.39	223.02
60	339.84	326.27	311.52	295.59	277.30	259.60	240.13	220.66	199.42	177.00
65	271.40	259.60	247.21	233.64	218.89	202.37	187.62	171.10	153.40	135.70
70	201.78	194.11	184.67	174.05	162.25	149.86	137.47	124.49	110.33	97.35
75	138.06	132.16	125.67	118.00	110.33	100.89	92.04	82.60	73.16	63.72
80	80.83	77.88	74.34	69.03	63.72	58.41	52.51	46.61	40.71	35.40
85	34.81	33.63	32.45	30.09	26.55	24.19	21.24	18.29	15.34	13.57
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

Vert. Horizontal Angles
 Angles

	<u>100</u>	<u>105</u>	<u>110</u>	<u>115</u>	<u>120</u>	<u>125</u>	<u>130</u>	<u>135</u>	<u>140</u>	<u>145</u>
0	551.06	551.06	551.06	551.06	551.06	551.06	551.06	551.06	551.06	551.06
5	544.57	542.21	539.85	537.49	535.72	533.36	531.59	529.23	527.46	525.69
10	531.59	526.28	520.97	515.66	510.35	505.04	500.32	495.60	491.47	487.34
15	512.71	503.86	495.01	486.75	477.90	469.05	460.79	451.94	444.27	436.60
20	488.52	476.72	463.74	450.76	437.78	424.80	411.82	397.66	385.27	372.88
25	458.43	442.50	425.39	407.69	389.99	371.11	352.82	333.35	316.24	300.90
30	423.03	403.56	381.73	358.72	335.71	312.11	289.10	267.27	248.98	233.64
35	382.91	359.31	333.35	305.62	279.07	253.11	229.51	210.04	194.70	182.31

IES INDOOR REPORT
PHOTOMETRIC FILENAME : VODE_107_WG_LO_35_C1.IES

CANDELA TABULATION - (Cont.)

40	338.66	312.11	282.61	253.70	225.38	201.19	181.13	165.20	153.99	145.14
45	292.05	263.14	233.05	204.73	179.36	159.30	143.96	132.75	124.49	118.00
50	244.26	215.94	187.62	162.84	142.19	126.85	115.64	107.38	101.48	97.35
55	197.65	172.28	148.09	128.03	112.10	100.89	93.22	87.32	83.19	79.65
60	155.17	133.93	113.87	99.12	87.32	79.65	73.75	69.62	66.67	64.31
65	117.41	100.89	86.14	74.93	66.67	60.77	57.23	53.69	51.92	49.56
70	84.37	71.39	61.36	53.69	48.38	44.25	41.30	39.53	37.76	36.58
75	54.87	47.79	39.53	34.81	31.27	28.91	27.14	25.37	24.78	23.60
80	30.09	24.78	21.24	18.29	16.52	15.34	14.16	13.57	12.98	12.39
85	10.62	8.26	7.08	5.90	5.31	5.31	4.72	4.13	4.13	3.54
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

Vert. Horizontal Angles

	<u>150</u>	<u>155</u>	<u>160</u>	<u>165</u>	<u>170</u>	<u>175</u>	<u>180</u>
0	551.06	551.06	551.06	551.06	551.06	551.06	551.06
5	524.51	523.33	522.15	520.97	520.38	519.79	519.79
10	483.21	480.26	477.31	474.95	473.77	472.59	472.59
15	429.52	423.62	418.31	414.18	411.23	409.46	408.87
20	361.67	352.82	344.56	338.07	333.35	330.40	329.81
25	287.33	276.12	266.68	259.60	254.88	251.93	251.34
30	221.25	211.22	203.55	198.24	194.70	192.34	191.75
35	172.28	165.20	159.89	156.35	153.99	152.22	151.63
40	138.65	133.34	129.80	127.44	125.08	124.49	123.90
45	113.28	110.33	107.38	105.02	103.84	103.25	102.66
50	93.81	91.45	89.09	87.32	86.14	85.55	85.55
55	77.29	74.93	73.16	71.98	71.39	70.21	70.21
60	61.95	60.77	59.00	57.82	57.23	56.64	56.64
65	48.38	47.20	46.02	45.43	44.84	44.25	44.25
70	35.40	34.22	33.63	33.04	32.45	32.45	32.45
75	23.01	22.42	21.83	21.24	21.24	21.24	21.24
80	11.80	11.80	11.21	11.21	11.21	11.21	11.21
85	3.54	3.54	2.95	2.95	2.95	2.95	2.95
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00

IES INDOOR REPORT
PHOTOMETRIC FILENAME : VODE_107_WG_LO_35_C1.IES

ZONAL LUMEN SUMMARY

Zone	Lumens	%Lamp	%Fixt
0-20	198.59	N.A.	14.00
0-30	411.72	N.A.	29.10
0-40	660.35	N.A.	46.60
0-60	1142.94	N.A.	80.70
0-80	1393.83	N.A.	98.40
0-90	1416.56	N.A.	100.00
10-90	1364.5	N.A.	96.30
20-40	461.76	N.A.	32.60
20-50	717.27	N.A.	50.60
40-70	646.41	N.A.	45.60
60-80	250.88	N.A.	17.70
70-80	87.07	N.A.	6.10
80-90	22.73	N.A.	1.60
90-110	0.00	N.A.	0.00
90-120	0.00	N.A.	0.00
90-130	0.00	N.A.	0.00
90-150	0.00	N.A.	0.00
90-180	0.00	N.A.	0.00
110-180	0.00	N.A.	0.00
0-180	1416.56	N.A.	100.00

Total Luminaire Efficiency = N.A.%

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	52.05
10-20	146.54
20-30	213.13
30-40	248.63
40-50	255.51
50-60	227.08
60-70	163.82
70-80	87.07
80-90	22.73
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00


IES INDOOR REPORT
PHOTOMETRIC FILENAME : VODE_107_WG_LO_35_C1.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	109	104	100	96	106	102	98	95	98	95	92	94	91	89	90	88	86	84
2	99	91	85	79	97	89	83	78	86	81	76	83	78	74	80	76	73	71
3	91	80	72	66	88	79	71	65	76	69	64	73	68	63	71	66	62	60
4	83	71	63	56	81	70	62	56	68	60	55	65	59	54	63	58	53	51
5	77	64	55	48	74	63	54	48	61	53	48	59	52	47	57	51	47	45
6	71	58	49	42	69	57	48	42	55	47	42	53	47	41	52	46	41	39
7	66	52	44	38	64	51	43	37	50	43	37	49	42	37	47	41	37	35
8	61	48	39	34	60	47	39	33	46	38	33	45	38	33	43	37	33	31
9	57	44	36	30	56	43	36	30	42	35	30	41	35	30	40	34	30	28
10	54	41	33	28	52	40	33	27	39	32	27	38	32	27	37	31	27	25

POLAR GRAPH



Maximum Candela = 625.4 Located At Horizontal Angle = 0, Vertical Angle = 25
1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (25) (Through Max. Cd.)